

reStructuredText Support in Trac

Trac supports using *reStructuredText* (RST) as an alternative to wiki markup in any context [WikiFormatting](#) is used.

From the reStructuredText webpage:

"reStructuredText is an easy-to-read, what-you-see-is-what-you-get plaintext markup syntax and parser system. It is useful for in-line program documentation (such as Python docstrings), for quickly creating simple web pages, and for standalone documents. reStructuredText is designed for extensibility for specific application domains."

Requirements

Note that to activate RST support in Trac, the python docutils package must be installed. If not already available on your operating system, you can download it at the [RST Website](#).

Install docutils using `easy_install docutils`. Do not use the package manager of your OS (e.g. `apt-get install python-docutils`), because Trac will not find docutils then.

More information on RST

- reStructuredText Website -- [?http://docutils.sourceforge.net/rst.html](http://docutils.sourceforge.net/rst.html)
 - RST Quick Reference -- [?http://docutils.sourceforge.net/docs/rst/quickref.html](http://docutils.sourceforge.net/docs/rst/quickref.html)
-

Using RST in Trac

To specify that a block of text should be parsed using RST, use the *rst* processor.

TracLinks in reStructuredText

- Trac provides a custom RST directive `trac::` to allow [TracLinks](#) from within RST text.

Example:

```
{{{
#!rst
This is a reference to |a ticket|

.. |a ticket| trac:: #42
}}}
```

- Trac allows an even easier way of creating [TracLinks](#) in RST, using the custom `:trac:` role.

Example:

```
{{{
#!rst
This is a reference to ticket `#12`:trac:

To learn how to use Trac, see `TracGuide`:trac:
}}}
```

For a complete example of all uses of the `:trac:` role, please see [WikiRestructuredTextLinks](#).

Syntax highlighting in reStructuredText

There is a directive for doing [TracSyntaxColoring](#) in RST as well. The directive is called `code-block`

Example

```
{{{
#!rst

.. code-block:: python

    class Test:

        def TestFunction(self):
            pass

}}}
```

Will result in the below.

```
.. code-block:: python

class Test:

    def TestFunction(self):
        pass
```

Wiki Macros in reStructuredText

For doing [Wiki Macros](#) in RST you use the same directive as for syntax highlighting i.e `code-block`. To work you must use a version of `trac` that has [?#801](#) applied.

Wiki Macro Example

```
{{{
#!rst

.. code-block:: RecentChanges

    Trac,3

}}}
```

Will result in the below:

Apr 24, 2020

- ◆ [TracWorkflow](#) (diff)
- ◆ [TracWiki](#) (diff)
- ◆ [TracUpgrade](#) (diff)

Or a more concise Wiki Macro like syntax is also available:

```
{{{
#!rst
```

```
:code-block:`RecentChanges:Trac,3`
}}}
```

Bigger RST Example

The example below should be mostly self-explanatory:

```
{{{
#!rst
FooBar Header
=====
reStructuredText is nice. It has its own webpage_.

A table:

=====  =====  =====
      Inputs      Output
-----
      A          B      A or B
=====
False  False  False
True   False  True
False  True   True
True   True   True
=====

RST TracLinks
-----

See also ticket `#42`:trac:.

.. _webpage: http://docutils.sourceforge.net/rst.html
}}}
```

Results in:

```
FooBar Header
=====
reStructuredText is nice. It has its own webpage_.

A table:

=====  =====  =====
      Inputs      Output
-----
      A          B      A or B
=====
False  False  False
True   False  True
False  True   True
True   True   True
=====

RST TracLinks
-----

See also ticket `#42`:trac:.

.. _webpage: http://docutils.sourceforge.net/rst.html
```

See also: [WikiRestructuredTextLinks](#), [WikiProcessors](#), [WikiFormatting](#)