

# The Trac Configuration File

## Error: Macro TracGuideToc(None) failed

```
'NoneType' object has no attribute 'find'
```

Trac configuration is done by editing the `trac.ini` config file, located in `<projectenv>/conf/trac.ini`.

## Global Configuration

Since version 0.9, Trac can also read the configuration from a global `trac.ini` file. These global options will then be merged with the environment-specific options, where local options override global options.

The global configuration is by default located in `$prefix/share/trac/conf/trac.ini`. It can be moved to a different location (for example, `/etc/trac.ini`), but that requires changing the file `trac/siteconfig.py` which gets created when Trac is installed.

## Reference

This is a brief reference of available configuration options.

### [attachment]

<u>max_size</u>	Maximum allowed file size (in bytes) for attachments.	262144
<u>max_zip_size</u>	Maximum allowed total size (in bytes) for an attachment list to be downloadable as a <code>.zip</code> . Set this to -1 to disable download as <code>.zip</code> . (since 1.0)	2097152
	Whether attachments should be rendered in the browser, or only made downloadable.	
<u>render_unsafe_content</u>	Pretty much any file may be interpreted as HTML by the browser, which allows a malicious user to attach a file containing cross-site scripting attacks.	disabled
	For public sites where anonymous users can create attachments it is recommended to leave this option disabled.	

### [browser]

	Enable colorization of the <i>age</i> column.	
<u>color_scale</u>	This uses the same color scale as the source code annotation: blue is older, red is newer.	enabled
<u>downloadable_paths</u>	List of repository paths that can be downloaded.	/trunk,/branches/*,/tags/*
	Leave this option empty if you want to disable all downloads, otherwise set it to a comma-separated list of authorized paths (those paths are glob patterns, i.e. "*" can	

be used as a wild card). In a multi-repository environment, the path must be qualified with the repository name if the path does not point to the default repository (e.g. /reponame/trunk). Note that a simple prefix matching is performed on the paths, so aliases won't get automatically resolved.

<u>hide_properties</u>	Comma-separated list of version control properties to hide from the repository browser.	svk:merge
<u>intermediate_color</u>	(r,g,b) color triple to use for the color corresponding to the intermediate color, if two linear interpolations are used for the color scale (see <code>intermediate_point</code> ). If not set, the intermediate color between <code>oldest_color</code> and <code>newest_color</code> will be used.	(no default)
<u>intermediate_point</u>	If set to a value between 0 and 1 (exclusive), this will be the point chosen to set the <code>intermediate_color</code> for interpolating the color value.	(no default)
<u>newest_color</u>	(r,g,b) color triple to use for the color corresponding to the newest color, for the color scale used in <i>blame</i> or the browser <i>age</i> column if <code>color_scale</code> is enabled.	(255, 136, 136)
<u>oldest_color</u>	(r,g,b) color triple to use for the color corresponding to the oldest color, for the color scale used in <i>blame</i> or the browser <i>age</i> column if <code>color_scale</code> is enabled.	(136, 136, 255)
<u>oneliner_properties</u>	Comma-separated list of version control properties to render as oneliner wiki content in the repository browser.  Whether raw files should be rendered in the browser, or only made downloadable.	trac:summary
<u>render_unsafe_content</u>	Pretty much any file may be interpreted as HTML by the browser, which allows a malicious user to create a file containing cross-site scripting attacks.	disabled
<u>wiki_properties</u>	For open repositories where anyone can check-in a file, it is recommended to leave this option disabled.  Comma-separated list of version control properties to render as wiki content in the repository browser.	trac:description

## [changeset]

<u>max_diff_bytes</u>	Maximum total size in bytes of the modified files (their old size plus their new size) for which the changeset view will attempt to show the diffs inlined.	10000000
<u>max_diff_files</u>	Maximum number of modified files for which the changeset view will attempt to show the diffs inlined.	0
	Whether wiki formatting should be applied to changeset messages.	
<u>wiki_format_messages</u>	If this option is disabled, changeset messages will be rendered as pre-formatted text.	enabled

## [components]

This section is used to enable or disable components provided by plugins, as well as by Trac itself. The component to enable/disable is specified via the name of the option. Whether its enabled is determined by the option value; setting the value to `enabled` or `on` will enable the component, any other value (typically `disabled` or `off`) will disable the component.

The option name is either the fully qualified name of the components or the module/package prefix of the component. The former enables/disables a specific component, while the latter enables/disables any component in the specified package/module.

Consider the following configuration snippet:

```
[components]
trac.ticket.report.ReportModule = disabled
acct_mgr.* = enabled
```

The first option tells Trac to disable the report module. The second option instructs Trac to enable all components in the `acct_mgr` package. Note that the trailing wildcard is required for module/package matching.

To view the list of active components, go to the *Plugins* page on *About Trac* (requires `CONFIG_VIEW` permissions).

See also: TracPlugins

## [header\_logo]

<u>alt</u>	Alternative text for the header logo.	(please configure the [header_logo] section in trac.ini)
<u>height</u>	Height of the header logo image in pixels.	-1
<u>link</u>	URL to link to, from the header logo.	(no default)
<u>src</u>	URL of the image to use as header logo. It can be absolute, server relative or relative.	site/your_project_logo.png

If relative, it is relative to one of the `/chrome` locations:  
site/your-logo.png if your-logo.png is located in the `htdocs` folder within your TracEnvironment;  
common/your-logo.png if your-logo.png is located in the folder mapped to the htdocs\_location URL.  
Only specifying your-logo.png is equivalent to the

latter.

width Width of the header logo image in pixels.

-1

## [http-headers]

Headers to be added to the HTTP request. (*since 1.2.3*)

The header name must conform to RFC7230 and the following reserved names are not allowed: content-type, content-length, location, etag, pragma, cache-control, expires.

## [inherit]

Path to the *shared htdocs directory*.

Static resources in that directory are mapped to /chrome/shared under the environment URL, in addition to common and site locations.

htdocs\_dir

(no  
default)

This can be useful in site.html for common interface customization of multiple Trac environments.

Non-absolute paths are relative to the Environment `conf` directory. (*since 1.0*)

Path to the *shared plugins directory*.

plugins\_dir

Plugins in that directory are loaded in addition to those in the directory of the environment `plugins`, with this one taking precedence.

(no  
default)

Non-absolute paths are relative to the Environment `conf` directory.

Path to the *shared templates directory*.

templates\_dir

Templates in that directory are loaded in addition to those in the environments `templates` directory, but the latter take precedence.

(no  
default)

Non-absolute paths are relative to the Environment `conf` directory.

## [intertrac]

This section configures InterTrac prefixes. Options in this section whose name contain a `.` define aspects of the InterTrac prefix corresponding to the option name up to the `.`. Options whose name don't contain a `.` define an alias.

The `.url` is mandatory and is used for locating the other Trac. This can be a relative URL in case that Trac environment is located on the same server.

The `.title` information is used for providing a useful tooltip when moving the cursor over an InterTrac link.

Example configuration:

```
[intertrac]
# -- Example of setting up an alias:
t = trac

# -- Link to an external Trac:
trac.title = Edgewall's Trac for Trac
trac.url = http://trac.edgewall.org
```

## [interwiki]

Every option in the [interwiki] section defines one InterWiki prefix. The option name defines the prefix. The option value defines the URL, optionally followed by a description separated from the URL by whitespace. Parametric URLs are supported as well.

### Example:

```
[interwiki]
MeatBall = http://www.usemod.com/cgi-bin/mb.pl?
PEP = http://www.python.org/peps/pep-$1.html Python Enhancement Proposal $1
tsvn = tsvn: Interact with TortoiseSvn
```

## [logging]

log\_file If log\_type is file, this should be a path to the log-file. Relative paths are resolved relative to the log directory of the environment. trac.log  
Custom logging format.

If nothing is set, the following will be used:

```
Trac[$(module)s] $(levelname)s: $(message)s
```

In addition to regular key names supported by the Python logger library one could use:

log\_format (no default)

- \$(path)s the path for the current environment
- \$(basename)s the last path component of the current environment
- \$(project)s the project name

Note the usage of \$(...)s instead of %(...)s as the latter form would be interpreted by the ConfigParser itself.

Example: \$(thread)d Trac[\$(basename)s:\$(module)s]  
\$(levelname)s: \$(message)s

Level of verbosity in log.

log\_level DEBUG  
Should be one of (CRITICAL, ERROR, WARNING, INFO, DEBUG).

Logging facility to use.

log\_type none  
Should be one of (none, file, stderr, syslog, winlog).

## [mainnav]

Configures the main navigation bar, which by default contains *Wiki*, *Timeline*, *Roadmap*, *Browse Source*, *View Tickets*, *New Ticket*, *Search* and *Admin*.

The label, href, and order attributes can be specified. Entries can be disabled by setting the value of the navigation item to disabled.

The following example renames the link to WikiStart to *Home*, links the *View Tickets* entry to a specific report and disables the *Search* entry.

```
[mainnav]
```

```
wiki.label = Home
tickets.href = /report/24
search = disabled
```

See [TracNavigation](#) for more details.

## [metanav]

Configures the meta navigation entries, which by default are *Login*, *Logout*, *Preferences*, *Help/Guide* and *About Trac*. The allowed attributes are the same as for [mainnav]. Additionally, a special entry is supported - `logout.redirect` is the page the user sees after hitting the logout button. For example:

```
[metanav]
logout.redirect = wiki/Logout
```

See [TracNavigation](#) for more details.

## [milestone]

<u>default_group_by</u>	Default field to use for grouping tickets in the grouped progress bar. (since 1.2)	component
<u>default_retarget_to</u>	Default milestone to which tickets are retargeted when closing or deleting a milestone. (since 1.1.2)	(no default)
<u>stats_provider</u>	Name of the component implementing ITicketGroupStatsProvider, which is used to collect statistics on groups of tickets for display in the milestone views.	DefaultTicketGroupStatsProvider

## [milestone-groups]

As the workflow for tickets is now configurable, there can be many ticket states, and simply displaying closed tickets vs. all the others is maybe not appropriate in all cases. This section enables one to easily create *groups* of states that will be shown in different colors in the milestone progress bar.

Note that the groups can only be based on the ticket *status*, nothing else. In particular, it's not possible to distinguish between different closed tickets based on the *resolution*.

Example configuration with three groups, *closed*, *new* and *active* (the default only has closed and active):

```
# the 'closed' group correspond to the 'closed' tickets
closed = closed

# .order: sequence number in the progress bar
closed.order = 0

# .query_args: optional parameters for the corresponding
#               query. In this example, the changes from the
#               default are two additional columns ('created' and
#               'modified'), and sorting is done on 'created'.
closed.query_args = group=resolution,order=time,col=id,col=summary,col=owner,col=type,col=priori

# .overall_completion: indicates groups that count for overall
#                       completion percentage
closed.overall_completion = true
```

## [mainnav]

```

new = new
new.order = 1
new.css_class = new
new.label = new

# Note: one catch-all group for other statuses is allowed
active = *
active.order = 2

# .css_class: CSS class for this interval
active.css_class = open

# .label: displayed label for this group
active.label = in progress

```

The definition consists in a comma-separated list of accepted status. Also, '\*' means any status and could be used to associate all remaining states to one catch-all group.

The CSS class can be one of: new (yellow), open (no color) or closed (green). Other styles can easily be added using custom CSS rule: `table.progress td.<class> { background: <color> }` to a [site/style.css](#) file for example.

## [mimeviewer]

<u>max_preview_size</u>	Maximum file size for HTML preview.	262144
<u>mime_map</u>	List of additional MIME types and keyword mappings. Mappings are comma-separated, and for each MIME type, there's a colon (":") separated list of associated keywords or file extensions.	text/x-dylan:dylan,text/x-idl:ice,text/x
<u>mime_map_patterns</u>	List of additional MIME types associated to filename patterns. Mappings are comma-separated, and each mapping consists of a MIME type and a Python regexp used for matching filenames, separated by a colon (":"). (since 1.0)	text/plain:README(?!\.rst)   INSTALL(?!\.r
<u>pygments_default_style</u>	The default style to use for Pygments syntax highlighting.	trac
<u>pygments_modes</u>	List of additional MIME types known by Pygments.	(no default)
	For each, a tuple <code>mimetype:mode:quality</code> has to be specified, where <code>mimetype</code> is the MIME type, <code>mode</code> is the corresponding Pygments mode to be used for	

the conversion and quality is the quality ratio associated to this conversion. That can also be used to override the default quality ratio used by the Pygments render.

tab width

Displayed tab width in file preview. 8

treat as binary

Comma-separated list of MIME types that should be treated as binary data. application/octet-stream, application/pdf

## [notification]

admit domains

Comma-separated list of domains that should be considered as valid for email addresses (such as localdomain). (no default)

Width of ambiguous characters that should be used in the table of the notification mail.

ambiguous char width

If single, the same width as characters in US-ASCII. This is expected by most users. If double, twice the width of US-ASCII characters. This is expected by CJK users. (since 0.12.2) single

batch subject template

Like ticket\_subject\_template but for batch modifications. (since 1.0) \${prefix} Batch modify: \${tickets\_descr}

default format.email

Default format to distribute email notifications. text/plain

email address resolvers

Comma separated list of email resolver components in the order they will be called. If an email address is resolved, the remaining resolvers will not be called. SessionEmailResolver  
Name of the component implementing IEmailSender.

email sender

This component is used by the notification system to send emails. Trac currently provides SmtplibEmailSender for connecting to an SMTP server, and SendmailEmailSender for running a sendmail-compatible executable. (since 0.12) SmtplibEmailSender

ignore domains

Comma-separated list of domains that should not be considered part of email addresses (for usernames with Kerberos domains). (no default)

message id hash

Hash algorithm to create unique Message-ID header. (since 1.0.13) md5

mime encoding

Specifies the MIME encoding scheme for emails. none

Supported values are: none, the default value which uses 7-bit encoding if the text is plain



ASCII or 8-bit otherwise. `base64`, which works with any kind of content but may cause some issues with touchy anti-spam/anti-virus engine. `qp` or `quoted-printable`, which works best for european languages (more compact than `base64`) if 8-bit encoding cannot be used.

Path to the sendmail executable.

<u>sendmail_path</u>	The sendmail program must accept the <code>-i</code> and <code>-f</code> options.	sendmail
	(since 0.12)	
<u>smtp_always_bcc</u>	Comma-separated list of email addresses to always send notifications to. Addresses are not public (Bcc:).	(no default)
<u>smtp_always_cc</u>	Comma-separated list of email addresses to always send notifications to. Addresses can be seen by all recipients (Cc:).	(no default)
<u>smtp_default_domain</u>	Default host/domain to append to addresses that do not specify one. Fully qualified addresses are not modified. The default domain is appended to all username/login for which an email address cannot be found in the user settings.	(no default)
<u>smtp_enabled</u>	Enable email notification. Sender address to use in notification emails.	disabled
<u>smtp_from</u>	At least one of <code>smtp_from</code> and <code>smtp_replyto</code> must be set, otherwise Trac refuses to send notification mails.	trac@localhost
<u>smtp_from_author</u>	Use the author of the change as the sender in notification emails (e.g. reporter of a new ticket, author of a comment). If the author hasn't set an email address, <code>smtp_from</code> and <code>smtp_from_name</code> are used instead. (since 1.0)	disabled
<u>smtp_from_name</u>	Sender name to use in notification emails.	(no default)
<u>smtp_password</u>	Password for authenticating with SMTP server.	(no default)
<u>smtp_port</u>	SMTP server port to use for email notification. Reply-To address to use in notification emails.	25
<u>smtp_replyto</u>	At least one of <code>smtp_from</code> and <code>smtp_replyto</code> must be set, otherwise Trac refuses to send notification mails.	trac@localhost
<u>smtp_server</u>	SMTP server hostname to use for email notifications.	localhost
<u>smtp_subject_prefix</u>	Text to prepend to subject line of notification emails.	__default__

	If the setting is not defined, then [ <code>\$project_name</code> ] is used as the prefix. If no prefix is desired, then specifying an empty option will disable it.	
<u>smtp_user</u>	Username for authenticating with SMTP server.	(no default)
<u>ticket_subject_template</u>	A Genshi text template snippet used to get the notification subject.	<code>\${prefix}</code> <code>#{ticket.id}:</code> <code>\${summary}</code>
	The template variables are documented on the <a href="#">TracNotification</a> page.	
	Addresses in the To and Cc fields are visible to all recipients.	
<u>use_public_cc</u>		disabled
	If this option is disabled, recipients are put in the Bcc list.	
	Permit email address without a host/domain (i.e. username only).	
<u>use_short_addr</u>	The SMTP server should accept those addresses, and either append a FQDN or use local delivery. See also <code>smtp_default_domain</code> . Do not use this option with a public SMTP server.	disabled
<u>use_tls</u>	Use SSL/TLS to send notifications over SMTP.	disabled

## [notification-subscriber]

The notifications subscriptions are controlled by plugins. All `INotificationSubscriber` components are in charge. These components may allow to be configured via this section in the `trac.ini` file.

See [TracNotification](#) for more details.

Available subscribers:

Subscriber	Description
<code>AlwaysEmailSubscriber</code>	
<code>CarbonCopySubscriber</code>	Ticket that I'm listed in the CC field is modified
<code>NewTicketSubscriber</code>	Any ticket is created
<code>TicketOwnerSubscriber</code>	Ticket that I own is created or modified
<code>TicketPreviousUpdatersSubscriber</code>	Ticket that I previously updated is modified
<code>TicketReporterSubscriber</code>	Ticket that I reported is modified
<code>TicketUpdaterSubscriber</code>	I update a ticket

## [project]

<u>admin</u>	E-Mail address of the project's (no default) administrator.
<u>admin_trac_url</u>	Base URL of a .

Trac instance  
where errors in  
this Trac  
should be  
reported.

This can be an  
absolute or  
relative URL,  
or '.' to  
reference this  
Trac instance.  
An empty value  
will disable the  
reporting  
buttons.

descr Short  
description of My example project  
the project.

footer Page footer text Visit the Trac open source project at  
(right-aligned). `href="http://trac.edgewall.org/"`><http://trac.edgewall.org/>

icon URL of the  
icon of the common/trac.ico  
project.

name Name of the  
project. My Project

url URL of the  
main project  
web site,  
usually the  
website in  
which the (no default)  
base\_url  
resides. This is  
used in  
notification  
e-mails.

## [pygments-lexer]

Configure Pygments [?lexer](#) options.

For example, to set the [?PhpLexer](#) options `startinline` and `funcnamehighlighting`:

```
[pygments-lexer]
php.startinline = True
php.funcnamehighlighting = True
```

The lexer name is derived from the class name, with `Lexer` stripped from the end. The lexer *short names* can also be used in place of the lexer name.

## [query]

<u>default_anonymous_query</u>	The default query for anonymous users. The query is either in <u>query language</u> syntax, or a URL query string starting with ? as used in query: <u>Trac links</u> .	status!=closed&cc~=\$USER
<u>default_query</u>	The default query for authenticated users. The query is either in <u>query language</u> syntax, or a URL query string starting with ? as used in query: <u>Trac links</u> .	status!=closed&owner=\$USER
<u>items_per_page</u>	Number of tickets displayed per page in ticket queries, by default.	100
<u>ticketlink_query</u>	The base query to be used when linkifying values of ticket fields. The query is a URL query string starting with ? as used in query: <u>Trac links</u> . (since 0.12)	?status!=closed

## [report]

<u>items_per_page</u>	Number of tickets displayed per page in ticket reports, by default.	100
<u>items_per_page_rss</u>	Number of tickets displayed in the rss feeds for reports.	0

## [repositories]

One of the alternatives for registering new repositories is to populate the [repositories] section of the trac.ini.

This is especially suited for setting up convenience aliases, short-lived repositories, or during the initial phases of an installation.

See TracRepositoryAdmin for details about the format adopted for this section and the rest of that page for the other alternatives.

(since 0.12)

## [revisionlog]

<u>default_log_limit</u>	Default value for the limit argument in the <u>TracRevisionLog</u> .	100
<u>graph_colors</u>	Comma-separated list of colors to use for the <u>TracRevisionLog</u> graph display. (since 1.0)	#cc0, #0c0, #0cc, #00c, #c0c, #c00

## [roadmap]

<u>stats_provider</u>	Name of the component implementing ITicketGroupStatsProvider, which is used to collect statistics on groups of tickets for display in the roadmap views.	DefaultTicketGroupStatsProvider
-----------------------	--	---------------------------------

## [search]

	Specifies which search filters should be disabled by default on the search page. This will also restrict the filters for the quick search function. The filter names defined by default components are: <code>wiki, ticket, milestone</code> and <code>changeset</code> . For plugins, look for their implementation of the <code>ISearchSource</code> interface, in the <code>get_search_filters()</code> method, the first member of returned tuple. Once disabled, search filters can still be manually enabled by the user on the search page. ( <i>since 0.12</i> )	(no default)
<u>default disabled filters</u>		
<u>min query length</u>	Minimum length of query string allowed when performing a search.	3

## [sqlite]

<u>extensions</u>	Paths to <u>sqlite extensions</u> . The paths may be absolute or relative to the Trac environment. ( <i>since 0.12</i> )	(no default)
-------------------	--	--------------

## [svn]

<u>authz_file</u>	The path to the Subversion <u>authorization (authz) file</u> . To enable authz permission checking, the <code>AuthzSourcePolicy</code> permission policy must be added to <code>[trac] permission_policies</code> . Non-absolute paths are relative to the Environment <code>conf</code> directory.	(no default)
<u>authz_module_name</u>	The module prefix used in the <code>authz_file</code> for the default repository. If left empty, the global section is used.	(no default)
<u>branches</u>	Comma separated list of paths categorized as branches. If a path ends with '*', then all the directory entries found below that path will be included. Example: <code>/trunk, /branches/*, /projectAlpha/trunk, /sandbox/*</code>	<code>trunk, branches/*</code>
<u>eol_style</u>	End-of-Line character sequences when <code>svn:eol-style</code> property is native.  If <code>native</code> , substitute with the native EOL marker on the server. Otherwise, if <code>LF</code> , <code>CRLF</code> or <code>CR</code> , substitute with the specified EOL marker.  ( <i>since 1.0.2</i> ) Comma separated list of paths categorized as tags.	<code>native</code>
<u>tags</u>	If a path ends with '*', then all the directory entries found below that path will be included. Example: <code>/tags/*, /projectAlpha/tags/A-1.0, /projectAlpha/tags/A-v1.1</code>	<code>tags/*</code>

## [svn:externals]

The TracBrowser for Subversion can interpret the `svn:externals` property of folders. By default, it only turns the URLs into links as Trac can't browse remote repositories.

However, if you have another Trac instance (or an other repository browser like ViewVC) configured to browse the target repository, then you can instruct Trac which other repository browser to use for which external URL. This mapping is done in the `[svn:externals]` section of the TracIni.

## Example:

```
[svn:externals]
1 = svn://server/repos1      http://trac/proj1/browser/$path?rev=$rev
2 = svn://server/repos2      http://trac/proj2/browser/$path?rev=$rev
3 = http://theirserver.org/svn/eng-soft  http://ourserver/viewvc/svn/$path/?pathrev=25914
4 = svn://anotherserver.com/tools_repository  http://ourserver/tracs/tools/browser/$path?rev=$rev
```

With the above, the `svn://anotherserver.com/tools_repository/tags/1.1/tools` external will be mapped to `http://ourserver/tracs/tools/browser/tags/1.1/tools?rev=` (and `rev` will be set to the appropriate revision number if the external additionally specifies a revision, see the [?SVN Book on externals](#) for more details).

Note that the number used as a key in the above section is purely used as a place holder, as the URLs themselves can't be used as a key due to various limitations in the configuration file parser.

Finally, the relative URLs introduced in [?Subversion 1.5](#) are not yet supported.

## [ticket]

<u>allowed empty fields</u>	Comma-separated list of select fields that can have an empty value. ( <i>since 1.1.2</i> )	milestone, version
<u>default cc</u>	Default cc: list for newly created tickets.	(no default)
<u>default component</u>	Default component for newly created tickets.	(no default)
<u>default description</u>	Default description for newly created tickets.	(no default)
<u>default keywords</u>	Default keywords for newly created tickets.	(no default)
<u>default milestone</u>	Default milestone for newly created tickets.	(no default)
<u>default owner</u>	Default owner for newly created tickets.	< default >
<u>default priority</u>	Default priority for newly created tickets.	major
<u>default resolution</u>	Default resolution for resolving (closing) tickets.	fixed
<u>default severity</u>	Default severity for newly created tickets.	(no default)
<u>default summary</u>	Default summary (title) for newly created tickets.	(no default)
<u>default type</u>	Default type for newly created tickets.	defect
<u>default version</u>	Default version for newly created tickets.	(no default)
<u>max comment size</u>	Maximum allowed comment size in characters.	262144
<u>max description size</u>	Maximum allowed description size in characters.	262144
<u>max summary size</u>	Maximum allowed summary size in characters. ( <i>since 1.0.2</i> )	262144
<u>preserve newlines</u>	Whether Wiki formatter should respect the new lines present in the Wiki text. If set to 'default', this is equivalent to 'yes' for new environments but keeps the old behavior for upgraded environments (i.e. 'no').	default
<u>restrict owner</u>		disabled

[svn:externals]

Make the owner field of tickets use a drop-down menu. Be sure to understand the performance implications before activating this option. See [Assign-to as Drop-Down List](#).

Please note that e-mail addresses are **not** obfuscated in the resulting drop-down menu, so this option should not be used if e-mail addresses must remain protected.

[workflow](#)

Ordered list of workflow controllers to use for ticket actions.

ConfigurableTicketWorkflow

## [ticket-custom]

In this section, you can define additional fields for tickets. See [TracTicketsCustomFields](#) for more details.

## [ticket-workflow]

The workflow for tickets is controlled by plugins. By default, there's only a `ConfigurableTicketWorkflow` component in charge. That component allows the workflow to be configured via this section in the `trac.ini` file. See [TracWorkflow](#) for more details.

## [timeline]

<a href="#">abbreviated messages</a>	Whether wiki-formatted event messages should be truncated or not.	enabled
<a href="#">changeset collapse events</a>	This only affects the default rendering, and can be overridden by specific event providers, see their own documentation. Whether consecutive changesets from the same author having exactly the same message should be presented as one event. That event will link to the range of changesets in the log view.	disabled
<a href="#">changeset long messages</a>	Whether wiki-formatted changeset messages should be multiline or not. If this option is not specified or is false and <code>wiki_format_messages</code> is set to true, changeset messages will be single line only, losing some formatting (bullet points, etc).	disabled
<a href="#">changeset show files</a>	Number of files to show (-1 for unlimited, 0 to disable). This can also be <code>location</code> , for showing the common prefix for the changed files.	0
<a href="#">default daysback</a>	Default number of days displayed in the Timeline, in days.	30
<a href="#">max daysback</a>	Maximum number of days (-1 for unlimited) displayable in the Timeline.	90
<a href="#">newticket formatter</a>	Which formatter flavor (e.g. 'html' or 'oneliner') should be used when presenting the description for new tickets. If 'oneliner', the [timeline] <code>abbreviated_messages</code> option applies.	oneliner
<a href="#">ticket show component</a>	Enable the display of component of tickets in the timeline.	disabled

	( <i>since 1.1.1</i> )	
<u>ticket show details</u>	Enable the display of all ticket changes in the timeline, not only open / close operations.	disabled
<b>[trac]</b>		
	Lifetime of the anonymous session, in days.	
<u>anonymous session lifetime</u>	Set the option to 0 to disable purging old anonymous sessions. ( <i>since 1.0.17</i> )	90
	Auth cookie domain attribute.	
<u>auth cookie domain</u>	The auth cookie can be shared among multiple subdomains by setting the value to the domain. ( <i>since 1.2</i> )	(no de
	Lifetime of the authentication cookie, in seconds.	
<u>auth cookie lifetime</u>	This value determines how long the browser will cache authentication information, and therefore, after how much inactivity a user will have to log in again. The value of 0 makes the cookie expire at the end of the browsing session. ( <i>since 0.12</i> )	0
<u>auth cookie path</u>	Path for the authentication cookie. Set this to the common base path of several Trac instances if you want them to share the cookie. ( <i>since 0.12</i> )	(no de
<u>auto preview timeout</u>	Inactivity timeout in seconds after which the automatic wiki preview triggers an update. This option can contain floating-point values. The lower the setting, the more requests will be made to the server. Set this to 0 to disable automatic preview. ( <i>since 0.12</i> )	2.0
<u>auto reload</u>	Automatically reload template files after modification.	disa
<u>backup dir</u>	Database backup location	db
	Reference URL for the Trac deployment.	
<u>base url</u>	This is the base URL that will be used when producing documents that will be used outside of the web browsing context, like for example when inserting URLs pointing to Trac resources in notification e-mails.	(no de
<u>check auth ip</u>	Whether the IP address of the user should be checked for authentication.	disa
<u>database</u>	Database connection <u>string</u> for this project	sqli
<u>debug sql</u>	Show the SQL queries in the Trac log, at DEBUG level.	disa
<u>default charset</u>	Charset to be used when in doubt.	utf-
<u>default date format</u>	The date format. Valid options are 'iso8601' for selecting ISO 8601 format, or leave it empty which means the default date format will be inferred from the browser's default language. ( <i>since 1.0</i> )	(no de
<u>default dateinfo format</u>	The date information format. Valid options are 'relative' for displaying relative format and 'absolute' for displaying absolute format. ( <i>since 1.0</i> )	rela
	Name of the component that handles requests to the base URL.	
<u>default handler</u>	Options include TimelineModule, RoadmapModule, BrowserModule, QueryModule, ReportModule, TicketModule and WikiModule.	Wiki
<u>default language</u>	The preferred language to use if no user preference has been set. ( <i>since 0.12.1</i> )	(no de
<u>default timezone</u>	The default timezone to use	(no de
<u>genshi cache size</u>	The maximum number of templates that the template loader will cache in memory. You may want to choose a higher value if your site uses a larger	128



number of templates, and you have enough memory to spare, or you can reduce it if you are short on memory.

Base URL for serving the core static resources below `/chrome/common/`.

It can be left empty, and Trac will simply serve those resources itself.

htdocs location

Advanced users can use this together with `trac-admin ... deploy <deploydir>` to allow serving the static resources for Trac directly from the web server. Note however that this only applies to the `<deploydir>/htdocs/common` directory, the other deployed resources (i.e. those from plugins) will not be made available this way and additional rewrite rules will be needed in the web server.

(no de

ignore\_auth\_case

Whether login names should be converted to lower case.  
Location of the jQuery JavaScript library (version 1.11.3).

disa

An empty value loads jQuery from the copy bundled with Trac.

jquery location

Alternatively, jQuery could be loaded from a CDN, for example:  
[?http://code.jquery.com/jquery-1.11.3.min.js](http://code.jquery.com/jquery-1.11.3.min.js),  
[?http://ajax.aspnetcdn.com/ajax/jquery/jquery-1.11.3.min.js](http://ajax.aspnetcdn.com/ajax/jquery/jquery-1.11.3.min.js) or  
[?https://ajax.googleapis.com/ajax/libs/jquery/1.11.3/jquery.min.js](https://ajax.googleapis.com/ajax/libs/jquery/1.11.3/jquery.min.js).

(no de

(since 1.0)

Location of the jQuery UI JavaScript library (version 1.11.4).

An empty value loads jQuery UI from the copy bundled with Trac.

jquery ui location

Alternatively, jQuery UI could be loaded from a CDN, for example:  
[?https://ajax.googleapis.com/ajax/libs/jqueryui/1.11.4/jquery-ui.min.js](https://ajax.googleapis.com/ajax/libs/jqueryui/1.11.4/jquery-ui.min.js) or  
[?http://ajax.aspnetcdn.com/ajax/jquery.ui/1.11.4/jquery-ui.min.js](http://ajax.aspnetcdn.com/ajax/jquery.ui/1.11.4/jquery-ui.min.js).

(no de

(since 1.0)

Location of the theme to be used with the jQuery UI JavaScript library (version 1.11.4).

An empty value loads the custom Trac jQuery UI theme from the copy bundled with Trac.

jquery ui theme location

(no de

Alternatively, a jQuery UI theme could be loaded from a CDN, for example:  
[?https://ajax.googleapis.com/ajax/libs/jqueryui/1.11.4/themes/start/jquery-ui.css](https://ajax.googleapis.com/ajax/libs/jqueryui/1.11.4/themes/start/jquery-ui.css)  
or [?http://ajax.aspnetcdn.com/ajax/jquery.ui/1.11.4/themes/start/jquery-ui.css](http://ajax.aspnetcdn.com/ajax/jquery.ui/1.11.4/themes/start/jquery-ui.css).

(since 1.0)

never\_obfuscate\_mailto

Never obfuscate `mailto:` links explicitly written in the wiki, even if `show_email_addresses` is false or the user doesn't have `EMAIL_VIEW` permission.

disa

permission\_policies

List of components implementing `IPermissionPolicy`, in the order in which they will be applied. These components manage fine-grained access control to Trac resources.

Read

permission\_store

Name of the component implementing `IPermissionStore`, which is used for managing user and group permissions.

Defa

<u>request_filters</u>	Ordered list of filters to apply to all requests.	(no de
<u>resizable_textareas</u>	Make <textarea> fields resizable. Requires JavaScript. ( <i>since 0.12</i> )	enab
	Restrict cookies to HTTPS connections.	
<u>secure_cookies</u>	When true, set the <code>secure</code> flag on all cookies so that they are only sent to the server on HTTPS connections. Use this if your Trac instance is only accessible through HTTPS.	disa
<u>show_email_addresses</u>	Show email addresses instead of usernames. If false, email addresses are obfuscated for users that don't have EMAIL_VIEW permission.	disa
<u>show_full_names</u>	Show full names instead of usernames. ( <i>since 1.2</i> )	enab
<u>show_ip_addresses</u>	Show IP addresses for resource edits (e.g. wiki). Since 1.0.5 this option is deprecated and will be removed in 1.3.1.	disa
<u>timeout</u>	Timeout value for database connection, in seconds. Use '0' to specify <i>no timeout</i> .	20
	Optionally use <code>[trac] base_url</code> for redirects.	
<u>use_base_url_for_redirect</u>	In some configurations, usually involving running Trac behind a HTTP proxy, Trac can't automatically reconstruct the URL that is used to access it. You may need to use this option to force Trac to use the <code>base_url</code> setting also for redirects. This introduces the obvious limitation that this environment will only be usable when accessible from that URL, as redirects are frequently used.	disa
<u>use_chunked_encoding</u>	If enabled, send contents as chunked encoding in HTTP/1.1. Otherwise, send contents with <code>Content-Length</code> header after entire of the contents are rendered. ( <i>since 1.0.6</i> )	disa
<u>use_xsendfile</u>	When true, send a <code>X-Sendfile</code> header and no content when sending files from the filesystem, so that the web server handles the content. This requires a web server that knows how to handle such a header, like Apache with <code>mod_xsendfile</code> or <code>lighttpd</code> . ( <i>since 1.0</i> )	disa
<u>wiki_toolbars</u>	Add a simple toolbar on top of Wiki <textarea>s. ( <i>since 1.0.2</i> )	enab
<u>xsendfile_header</u>	The header to use if <code>use_xsendfile</code> is enabled. If Nginx is used, set <code>X-Accel-Redirect</code> . ( <i>since 1.0.6</i> )	X-Se

## [versioncontrol]

<u>allowed_repository_dir_prefixes</u>	Comma-separated list of allowed prefixes for repository directories when adding and editing repositories in the repository admin panel. If the list is empty, all repository directories are allowed. ( <i>since 0.12.1</i> )	(no default)
<u>default_repository_type</u>	Default repository connector type.	
	This is used as the default repository type for repositories defined in the <code>repositories</code> section or using the "Repositories" admin panel. ( <i>since 0.12</i> )	svn

## [wiki]

<u>default_edit_area_height</u>	Default height of the textarea on the wiki edit page. ( <i>Since 1.1.5</i> )	20
<u>ignore_missing_pages</u>	Enable/disable highlighting <u>CamelCase</u> links to missing	disabled

<u>max_size</u>	<p>pages.</p> <p>Maximum allowed wiki page size in characters. 262144</p> <p>Enable/disable the use of unsafe HTML tags such as <code>&lt;script&gt;</code> or <code>&lt;embed&gt;</code> with the HTML <u>WikiProcessor</u>.</p>
<u>render_unsafe_content</u>	<p>disabled</p> <p>For public sites where anonymous users can edit the wiki it is recommended to leave this option disabled.</p> <p>List of URIs considered "safe cross-origin", that will be rendered as <code>img</code> element without <code>crossorigin="anonymous"</code> attribute or used in <code>url()</code> of inline style attribute even if <code>data:[wiki]render_unsafe_content</code> is false (<i>since 1.0.15</i>).</p> <p>To make any origins safe, specify <code>"*"</code> in the list.</p>
<u>safe_origins</u>	
<u>safe_schemes</u>	<p>List of URI schemes considered "safe", that will be rendered as external links even if <code>[wiki]render_unsafe_content</code> is false. cvs, file, ftp, git, irc, http, https, news</p>
<u>split_page_names</u>	<p>Enable/disable splitting the <u>WikiPageNames</u> with space characters. disabled</p>

## [components]

(*since 0.9*)

This section is used to enable or disable components provided by plugins, as well as by Trac itself. The component to enable/disable is specified via the name of the option. Whether its enabled is determined by the option value; setting the value to `enabled` or `on` will enable the component, any other value (typically `disabled` or `off`) will disable the component.

The option name is either the fully qualified name of the components or the module/package prefix of the component. The former enables/disables a specific component, while the latter enables/disables any component in the specified package/module.

Consider the following configuration snippet:

```
[components]
trac.ticket.report.ReportModule = disabled
webadmin.* = enabled
```

The first option tells Trac to disable the report module. The second option instructs Trac to enable all components in the `webadmin` package. Note that the trailing wildcard is required for module/package matching.

See the *Plugins* page on *About Trac* to get the list of active components (requires `CONFIG_VIEW` permissions.)

See also: TracPlugins

*Note that prior to Trac r2335 (that applies to 0.9b1 and 0.9b2), you would use a `[disabled_components]` section instead. See a ?previous version of this page for the details.*

---

See also: TracGuide, TracAdmin, TracEnvironment